



Apcotex[®] XNB 500

CHEMICAL DESCRIPTION

Apcotex XNB 500 is a carboxylated butadiene-acrylonitrile copolymer latex used for making fabric supported industrial gloves.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

ADVANTAGES

- Excellent for seamless and cut & sewn gloves
- Provide high abrasion resistance
- Fast gelling for good productivity
- Low thickener demand in compound
- Excellent compound stability

NOTE

Guidelines for compounding formulation and curing condition will be provided upon request.

PRODUCT SPECIFICATIONS

Appearance	Milky white pourable emulsion
Emulsifying System	Synthetic anionic
Total Solids (%)	44.0 ± 1.0
pH at 25°C	8.0 ± 1.0
Brookfield Viscosity DV (CPS) SP.1, 60 RPM at 25°C	100 Max.
Surface Tension (Dynes/cm) at 25°C	34.0 ± 3.0
Acrylonitrile Content	Medium
Antioxidant	Yes

STORAGE RECOMMENDATION

Store between temperatures of +5°C and +40°C.

Keep containers closed when not in use.

Protect from freezing and direct exposure to sunlight.

PDS-XNB 500-11-2020/Rev.2

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

Disclaimer : These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale