



Apcotex[®] XNB 600

CHEMICAL DESCRIPTION

Apcotex XNB 600 is a carboxylated butadiene-acrylonitrile copolymer latex used for making unsupported industrial gloves by coagulant dipping process.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

ADVANTAGES

- Excellent for making flock line industrial gloves
- Good tensile strength with flexibility
- High resistance against chemicals and oils
- Better abrasion and puncture resistance
- Fast gelling for good productivity
- Excellent compound stability

NOTE

Guidelines for compounding formulation and curing condition will be provided upon request.

PRODUCT SPECIFICATIONS

Appearance	Milky white pourable emulsion
Emulsifying System	Synthetic anionic
Total Solids (%)	44.0 ± 1.0
pH at 25°C	8.0 ± 1.0
Brookfield Viscosity DV (CPS) SP.1, 60 RPM at 25°C	100 Max.
Surface Tension (Dynes/cm) at 25°C	40.0 ± 5.0
Acrylonitrile Content	High
Antioxidant	Yes

STORAGE RECOMMENDATION

Store between temperatures of +5°C and +40°C.

Keep containers closed when not in use.

Protect from freezing and direct exposure to sunlight.

PDS-XNB 600-11-2020/Rev.2

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

Disclaimer : These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale