



Apcoflex[®] NVC155E

NBR:PVC Rubber Polyblend

CHEMICAL DESCRIPTION

Apcoflex[®] NVC155E* is a blend of Apcoflex NBR, PVC and Plasticiser in the ratio of 50:50:10.

It contains non-staining stabilizer and comes in Sheet form.

CAS No: 9003-18-3 : NBR

CAS No: 9002-86-2 : PVC

APPLICATIONS

Apcoflex[®] NVC155E is a polyblend of Nitrile Rubber and PVC. Hence, it provides Oil, Fuel, Thermal resistance as well as Ozone and environmental resistance. It is thus recommended for the manufacture of products suitable for out-door applications where high flow and gloss is desired.

It finds applications in the manufacture high hardness

Automotive and industrial goods

PRODUCT SPECIFICATIONS

PROPERTY	LIMITS
Volatile Matter,%	0.7 Max.
Mooney Viscosity, ML 1+4 @ 100°C, MU	55 - 65
Ash Content,%	1.0 Max.

SAFETY AND HANDLING

Apcoflex[®] NVC155E may contain traces of residual monomers, which may be released during processing at high temperatures. Therefore adequate ventilation should be employed in the processing areas.

PACKAGING AND SHELF-LIFE

These NVC sheets are wrapped in poly films and are then packed in woven sacks.

Appx. Dimensions (in): 30x 16x 5 (when packed)

Weight, kg : 35 kg net (when packed)

Recommended to store in original packaging, away from direct sources of heat and sunlight. These Polyblends will have a minimum of 24 months shelf-life under good storage practices.

* E grades are free from DOP and heavy metals.

PDS-NVC155E-18-09

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

Disclaimer : These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale