



## Apcoflex<sup>®</sup> NVC273E

NBR:PVC Rubber Polyblend

### CHEMICAL DESCRIPTION

Apcoflex<sup>®</sup> NVC273E\* is a blend of Apcoflex NBR and PVC in 70:30 ratio.

It contains non-staining stabilizer and comes in Sheet form.

CAS No: 9003-18-3 : NBR

CAS No: 9002-86-2 : PVC

### APPLICATIONS

Apcoflex<sup>®</sup> NVC273E is a high viscosity Polyblend of Nitrile Rubber with PVC and is specifically designed for low temperature applications; It provides Oil, Fuel, Thermal resistance as well as Ozone and environmental resistance.

It is recommended for the manufacture of extruded and molded products suitable for out-door applications in automotive and industrial applications.

This is cost effective, low ACN blend for general purpose automotive and industrial moulded and extruded products.

\* E grades are free from DOP and heavy metals.

### PRODUCT SPECIFICATIONS

PROPERTY	LIMITS
Volatile Matter,%	0.7 Max.
Mooney Viscosity, ML 1+4 @ 100°C, MU	60 - 70
Ash Content,%	1.0 Max.

### SAFETY AND HANDLING

Apcoflex<sup>®</sup> NVC273E may contain traces of residual monomers, which may be released during processing at high temperatures. Therefore adequate ventilation should be employed in the processing areas.

### PACKAGING AND SHELF-LIFE

These NVC sheets are wrapped in plastic films and are then packed in woven sacks.

Appx. Dimensions (in): 30x 16x 5 (when packed)

Weight, kg 35 kg net (when packed)

Recommended to store in original packaging, away from direct sources of heat and sunlight. These Polyblends will have a minimum of 24 months shelf-life under good storage practices

PDS-NVC273E-18-09