



# Technical Data Sheet

## Apcotex<sup>®</sup> C7610

### CHEMICAL DESCRIPTION

Apcotex C7610 is a specialty Styrene Acrylic Latex used as an admixture in cement mortar and concrete.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency

### APPLICATIONS/ADVANTAGES

- Bonding agent, cementitious waterproofing, repair mortar
- High resistance to water penetration
- External surface coating
- Offers good workability at reduced water/ cement ratio
- Improved bonding and adhesion to substrate. Improved toughness and flexibility

### SAFETY AND HANDLING

- General safety precautions such as goggles, gloves and face shields should be used while handling. (Refer MSDS for detail information).

### PRODUCT SPECIFICATIONS

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic and nonionic
Total Solids (%)	47.0 ± 0.5
pH at 25°C	9.0 ± 0.5
Brookfield Viscosity LVF (CPS) SP.1, 12 RPM at 25°C	200 Max
Surface Tension (Dynes/cm) at 25°C	40 ± 5.0
Specific Gravity	1.015 ± 0.005
Dilutability with water	Dilutable in any proportion
Compatibility	Compatible with Cement and Concrete mixture

### STORAGE RECOMMENDATIONS

- Store between temperatures of + 5°C and 40°C. Keep containers closed when not in use.
- Self-life: Six month from data of manufacturing provided stored under shade, away from direct heat and sunlight and well protected from freezing.
- Packing: 200 Kg HDPE Drums.

PDS C7610 - 2017-01

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

**Disclaimer :** These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale