



# Technical Data Sheet

## Apcotex® CB 6000

### CHEMICAL DESCRIPTION

Apcotex CB 6000 is a specialty Styrene Acrylic Latex used designed for medium stiff secondary and tertiary backing of tufted carpet.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

### APPLICATIONS/ADVANTAGES

- Secondary and tertiary backing of tufted carpets
- Excellent tuft lock strength in the tufted carpet
- Excellent filler compatibility and compound Stability
- Excellent combination of Stiffness and flexibility properties which will not allows cracks after bending.
- Good delamination strength in tertiary backing with tufted carpet
- Excellent lay-flat characteristics
- Low VOC and odour

### SAFETY AND HANDLING

- General safety precautions such as goggles, gloves and face shields should be used while handling. (Refer MSDS for detail information)

### PRODUCT SPECIFICATIONS

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic
pH at 25°C	7.5 ± 0.5
Brookfield Viscosity LVF (CPS) SP.2, 12 RPM at 25°C	1200 ± 500
Surface Tension (Dynes/cm) at 25°C	50 ± 5.0
Film appearance	Clear and Sl. Tacky
Bactericide	Present

### STORAGE RECOMMENDATIONS

- Store between temperatures of + 5°C and 40°C. Keep containers closed when not in use.
- Shelf-life: Six month from date of manufacturing provided stored under shade, away from direct heat and sunlight and well protected from freezing.
- Packing: 200 Kg HDPE Drums.

PDS – CB 6000 - 2019- 01

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

Disclaimer : These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale.