



Technical Data Sheet

Apcotex[®] PT800

CHEMICAL DESCRIPTION

Apcotex PT800 is a modified Carboxylated Styrene Butadiene latex specially developed for coating of varieties of Papers and Paperboards.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency..

PRODUCT SPECIFICATIONS

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic
Total Solids (%)	50.0 ± 1.0
pH at 25°C	6.5 ± 0.5
Brookfield Viscosity LVF (CPS) SP.1, 12 RPM at 25°C	150 - 500
Surface Tension (Dynes/cm) at 25°C	45 ± 3.0
Film Characteristics	Clear and slightly tacky
Compatibility	Compatible with other coating color substances

ADVANTAGES

- Excellent dry pick resistance
- Superior print performance of coated paper
- High sheet gloss and print gloss
- Excellent rheology at high shear rate
- Good runnability at high machine speeds
- Suitable for blade, bar and air knife coaters

STORAGE RECOMMENDATIONS

Store between temperatures of + 5°C and 40°C.Keep containers closed when not in use. Protect from freezing and direct exposure to sunlight

April .2013/Tech-F02/Rev.1

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

Disclaimer : These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale