



Technical Data Sheet

Apcotex[®] TY100

CHEMICAL DESCRIPTION

Apcotex TY100 is a copolymer of styrene-butadiene latex used for dipping of fabric for tyre cord, V-belts and conveyor belts. Its application also includes textile finishing and adhesive.

It is manufactured by emulsion polymerization method with state-of-the-art manufacturing facilities to produce consistent product.

PRODUCT SPECIFICATIONS

Appearance	Off white liquid
Emulsifying System	Synthetic anionic
Total Solids (%)	41.0 ± 1.0
pH at 25°C	11.0 ± 1.0
Brookfield Viscosity LVF (CPS) SP.1, 60 RPM at 25°C	40.0 ± 20.0
Surface Tension (Dynes/cm) at 25°C	59 ± 5.0
Coagulum (%)	0.05 Max.
Mechanical stability (gm/100cc)	0.3 Max.
ML ₁₊₄ @ 100°C (ASTM D1417)	90 Max

ADVANTAGES

- Excellent Mechanical stability and chemical stability
- Compatible with vinyl pyridine latex
- Aids in processing
- Excellent gloss development and good wet pick resistance
- Good tackiness properties
- Provide excellent film strength

STORAGE RECOMMENDATIONS

Store between temperatures of + 5°C and 40°C. Keep containers closed when not in use. Protect from freezing and direct exposure to sunlight

June .2016/Tech-F02/Rev.0

apcotex industries limited

Email  : info@apcotex.com

Web  : www.apcotex.com

Disclaimer : These suggestions and data are based on information that we believe to be reliable. They are given for information only and in good faith, but conditions and methods of use of our products are beyond our control. Apcotex recommends that the user determine the suitability of our materials and suggestions before using them on a commercial scale