

### **CHEMICAL DESCRIPTION**

Apcotex PB 400 is a specialty Styrene Acrylic Latex designed for soft secondary backing of tufted carpet.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

# **APPLICATIONS/ADVANTAGES**

- Secondary backing of tufted carpets.
- It can be use for tertiary backing of tufted carpets.
- Excellent tuft lock strength in the tufted carpet.
- Excellent filler compatibility and compound Stability.
- Good delamination strength in tertiary backing with tufted carpet.
- Excellent lay-flat characteristics.
- Low VOC and odour.

### **SAFETY AND HANDLING**

General safety precautions such as goggles, gloves and face shields should be used while handling. (Refer MSDS for detail information)

#### PRODUCT SPECIFICATIONS

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic
pH at 25°C	7.25 <u>+</u> 0.5
Brookfield Viscosity LVF (CPS) SP.2, 12 RPM at 25°C	1750 ± 750
Surface Tension (Dynes/cm) at 25°C	50 ± 5.0
Film Appearance	Clear and Tacky
Bactericide	Present

# STORAGE RECOMMENDATIONS

- Store between temperatures of + 5°C and 40°C.
- Keep containers closed when not in use.
- Shelf-life: Six months from the date of manufacturing provided stored under shade, away from direct heat and sunlight, and well protected from freezing.
- Packing: 200 Kg HDPE Drums.

For further information, call + 91 22277 70800

PDS - PB 400 - 2023 - 00

Apcotex Industries Limited info@apcotex.com www.apcotex.com

Taloja – Plot No.3/1, MIDC Industrial Area, Taloja-410208 Plant 2 Valia - Village Dungri, Taluka-Valia, Ankleshwar-393135