



CHEMICAL DESCRIPTION

Apcotex PC 200 is a Carboxylated Styrene-Butadiene Latex used as a binder for metalized paper coating and Non-Woven Carpets.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

ADVANTAGES

- Provides good binding strength.
- Excellent metalized gloss.
- Easy to use in Non-Woven Carpets.
- No undesirable odor in the finished carpet.
- Excellent compatibility with fillers like Calcium Carbonate, China Clay and co binders like Carboxy Methyl Cellulose (CMC), Synthetic Acrylic thickener.

PRODUCT SPECIFICATIONS

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic
Total Solids (%)	50.0 ± 1.0
pH at 25°C	9.0 ± 0.5
Brookfield Viscosity LVF (CPS) SP.1, 12 RPM at 25°C	300 Max
Surface Tension (Dynes/cm)at 25°C	39 ± 3.0
Film Characteristics	Clear and slightly tacky
Compatibility	Compatible with other coating color substances

STORAGE RECOMMENDATIONS

- Store between temperatures of + 5°C and 40°C.
- Keep containers closed when not in use.
- Protect from freezing and direct exposure to sunlight.

For further information, call + 91 22277 70800

PDS - PC200 - 2023 - 00

Apcotex Industries Limited
info@apcotex.com
www.apcotex.com

Plant 1
Taloja – Plot No.3/1, MIDC
Industrial Area, Taloja-410208

Plant 2
Valia - Village Dungri,
Taluka-Valia, Ankleshwar-393135

Disclaimer : These suggestions and data are based on the information that we believe to be reliable. They are given for the information only and in good faith, but conditions and methods of use of our product are beyond our control. Apcotex recommends that the user determine the suitability of our material and suggestions before using them for a commercial scale.