

Apcoflex® NL100

Anionic aqueous dispersion of a
Butadiene-Acrylonitrile copolymer

TECHNICAL DATA SHEET



KEY ADVANTAGES

- Contains non-staining antioxidant.
- Excellent Fuel & solvent Resistance.
- Excellent gloss development, moderate tackiness.
- Excellent Film strength.

APPLICATIONS

- Binder in Cork Sheets.
- Binder in Gaskets.
- Paper Saturation.
- Adhesives.

TYPICAL PROPERTIES

Type	Butadiene - acrylonitrile copolymer
pH	10.5
Total solids, %	40
Brookfield Viscosity, cps	55
CAS No.	9003-18-3
Mechanical Stability	Good

SAFETY AND HANDLING

This latex may contain traces of residual monomers, which may be released during processing at high temperatures. Adequate ventilation should be employed in the processing areas.

Please read the material safety data sheet (MSDS) prior to use. Copy can be obtained by contacting your Customer Service Representative.

PACKAGING, STORAGE AND SHELF-LIFE

Normal packaging is 200 litres plastic drums (closed head with two bungs). Bulk packaging is available.

Store in original packaging; Store at 41° to 104°F (5° to 40°C). Protect from freezing.

Typical shelf life is 6 months from the date of manufacture when stored as recommended.

For further information, call + 91 22277 70800

PDS - NL100 - 2023 - 00

Apcotex Industries Limited
info@apcotex.com
www.apcotex.com

Plant 1
Taloja – Plot No.3/1, MIDC
Industrial Area, Taloja-410208

Plant 2
Valia - Village Dungri,
Taluka-Valia, Ankleshwar-393135

Disclaimer : These suggestions and data are based on the information that we believe to be reliable. They are given for the information only and in good faith, but conditions and methods of use of our product are beyond our control. Apcotex recommends that the user determine the suitability of our material and suggestions before using them for a commercial scale.