



CHEMICAL DESCRIPTION

Apcotex PT800 is a modified Carboxylated Styrene Butadiene latex specially developed for coating of varieties of Papers and Paperboards.

It is manufactured by employing state-of-the-art emulsion polymerization technology ensuring product consistency.

ADVANTAGES

- Excellent dry pick resistance.
- Superior print performance of coated paper.
- High sheet gloss and print gloss.
- Excellent rheology at high shear rate.
- Good runnability at high machine speeds.
- Suitable for blade, bar and air knife coaters.

PRODUCT SPECIFICATIONS

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic
Total Solids (%)	50.0 ± 1.0
pH at 25°C	6.5 ± 0.5
Brookfield Viscosity LVF (CPS) SP.1, 12 RPM at 25°C	150 - 500
Surface Tension (Dynes/cm)at 25°C	45 ± 3.0
Film Characteristics	Clear and slightly tacky
Compatibility	Compatible with other coating color substances

STORAGE RECOMMENDATIONS

- Store between temperatures of + 5°C and 40°C.
- Keep containers closed when not in use.
- Protect from freezing and direct exposure to sunlight.

For further information, call + 91 22277 70800

PDS - PT800 - 2023 - 00

Apcotex Industries Limited
info@apcotex.com
www.apcotex.com

Plant 1
Taloja – Plot No.3/1, MIDC
Industrial Area, Taloja-410208

Plant 2
Valia - Village Dungri,
Taluka-Valia, Ankleshwar-393135

Disclaimer : These suggestions and data are based on the information that we believe to be reliable. They are given for the information only and in good faith, but conditions and methods of use of our product are beyond our control. Apcotex recommends that the user determine the suitability of our material and suggestions before using them for a commercial scale.